

Safe Storage
Diesel Storage & Dispensing
Canada

Kingspan

NEW
SERIES

More Robust.
More Durable.
More Secure...to do more.

Available from 200 – 430 litres



kingspan.ca/diesel

Kingspan

TruckMaster®

Portable Diesel Storage & Dispensing Solutions

Available from 200 – 430 litres

The New Series TruckMaster range has been specifically designed for the safe transportation of diesel fuel, allowing users the ultimate convenience to refuel remotely. This poly dispensing tank range is more robust, more durable and more secure than ever before.

Available from 200 – 430 litres, with a number of specification and dispensing options, the TruckMaster range suits a variety of applications including Agricultural, Construction and Forestry. Built from high-quality polyethylene, all tanks are resistant to structural damage, changing weather conditions and UV radiation.



40 Years Experience

40 YEARS

Tank Guarantee*

5 YEARS

ISO Compliant

ISO 9001:2015
ISO 14001:2015
BS OHSAS 18001:2007

Features and Benefits

Secure Lockable Lid

All TruckMasters come with a lockable lid that covers the entire dispensing equipment, with no parts like pumps, hoses or nozzles being exposed. It provides a more reliable protection against equipment damage or theft compared to traditional totes and barrels.

TM430/300 Equipment Specification

1. Tank
2. 12V Pump
3. Automatic nozzle (with optional flowmeter, if required)
4. Pressure relief vent
5. Delivery hose
6. Lockable lid**
7. Lifting lugs†
8. 4" Inspection lid††
9. Filling point†††
10. Internal LED Light†††
11. Gas Strut



Safe Transportation

The TM430 and TM200 litre low profile models feature an internal baffle wall which minimizes the movement of diesel while the tank is being transported.

Easy to Lift and Handle

As a lightweight portable tank, the TruckMasters give you flexibility and saves you time. The tanks are approved to be lifted through forklift pockets. The TM200 low profile TM430 models have integrated lifting eyes and lifting lugs which allows the tank to be lifted - even when full!



The Perfect Companion for your Truck

The TruckMaster tanks are designed for minimal footprint and height. It makes them the perfect add-on to your truck, as they only occupy a small space on the truck-bed and can be tied down between the wheel arches of the pick-up.

Model Selector

All dimensions and weights are an approximate only

* Two year on equipment
** Lid with integrated lock (TM200 Low Profile and TM430).
Lid with lockable latch, padlock not provided (TM200 and TM300)
† Available on TM200 Low Profile as an option and TM430 as standard
†† Available on TM200 Low Profile as an option and TM430 as standard
††† Available in different options TM430

TM200	
	
Capacity	200 litres
Length	600 mm
Width	800 mm
Height	620 mm
Weight	33 kg

TM200 low profile	
	
Capacity	200 litres
Length	1180 mm
Width	860 mm
Height	500 mm
Weight	46 kg

TM300	
	
Capacity	300 litres
Length	600 mm
Width	800 mm
Height	890 mm
Weight	45 kg

TM430	
	
Capacity	430 litres
Length	1180 mm
Width	860 mm
Height	910 mm
Weight	60 kg

Specification Options

TruckMaster®

DESCRIPTION / CAPACITY	TM200	TM200 LOW PROFILE	TM300	TM430
Level gauge				•
Ball valve on suction line		○		•
Suction line with mesh filter	•	•	•	•
12 V DC pump (max. flow rate 50 l/min)*	•	•	•	•
6 m power cable with battery clamps	•	•	•	•
4 m flexible delivery hose		•		•
3,7 m flexible delivery hose	•		•	
Automatic nozzle	•	•	•	•
Lid with integrated lock		•		•
Lid with lockable latch (padlock not provided)	•		•	
Lid with gas strut support				•
Vacuum and pressure relief vent	•	•	•	•
4 lifting lugs		○		•
Battery powered LED lamp		○		•
24 V DC pump (max. flow rate 50 L/min)*	○	○	○	○
24/12 DC pump (max. flow rate 70/35 L/min)*				○
12 V DC bipump (max. flow rate 85 L/min)*				○
Digital flowmeter fixed to the nozzle	○	○	○	○
Digital flowmeter fixed to the pump		○		○

• Standard accessories ○ Optional accessories

*Maximum across pump flow rate as defined by pump manufacturer. Actual flowrate will be less.



Head Office

Kingspan Water & Energy

180 Gilford Road, Portadown,
Co. Armagh, BT63 5LF, United Kingdom
T: +44 (0) 28 3836 4444
E: tankinfo.na@kingspan.com

The warranty is valid only if the product is used in accordance with the instructions given in the user manual and only if used for the intended purpose. Any modifications to the product without the written consent of the producer may render the warranty invalid. All included pictures are for illustration purposes only. We take every care to ensure that the information in this document is accurate at the point of publication, but with continuous product development, details are subject to alteration without notice.