

Safe Storage
Diesel Storage & Dispensing
USA

Kingspan

NEW
SERIES

More Robust.
More Durable.
More Secure...to do more.

Available from 53 – 114 gallons



kingspan.us/diesel


Kingspan

TruckMaster®

Portable Diesel Storage & Dispensing Solutions

Available from 53 –114 gallons

The New Series TruckMaster range has been specifically designed for the safe transportation of diesel fuel, allowing users the ultimate convenience to refuel remotely. This poly dispensing tank range is more robust, more durable and more secure than ever before.

Available from 53 –114 gallons, with a number of specification and dispensing options, the TruckMaster range suits a variety of applications including Agricultural, Construction and Forestry. Built from high-quality polyethylene, all tanks are resistant to structural damage, changing weather conditions and UV radiation.



Model Selector

Subject to manufacturing variation, all dimensions and weights are an approximate only.

* Two year on equipment

** Lid with integrated lock (TM53 Low Profile and TM114).

Lid with lockable latch, padlock not provided (TM53 and TM79)

† Available on TM53 Low Profile as an option and TM114 as standard

†† Available on TM53 Low Profile as an option and TM114 as standard

††† Available in different options TM114

TM53



Capacity	53 gallons
Length	24 inches
Width	32 inches
Height	25 inches
Weight	72 lbs

40 Years
Experience

40
YEARS

Tank
Guarantee*

5
YEARS

TM79

6

3

2

NEW Metal Hinge Technology

Features and Benefits

Secure Lockable Lid

All TruckMasters come with a lockable lid that covers the entire dispensing equipment, with no parts like pumps, hoses or nozzles being exposed. It provides a more reliable protection against equipment damage or theft compared to traditional totes and barrels.

TM114/79 Equipment Specification

1. Tank
2. 12V Pump
3. Automatic nozzle (with optional flowmeter, if required)
4. Pressure relief vent
5. Delivery hose
6. Lockable lid**
7. Lifting lugs†
8. 4" Inspection lid††
9. Filling point†††
10. Internal LED Light†††
11. Gas Strut



Safe Transportation

The TM114 and TM53 gallon low profile models feature an internal baffle wall which minimizes the movement of diesel while the tank is being transported.

Easy to Lift and Handle

As a lightweight portable tank, the TruckMasters give you flexibility and saves you time. The tanks are approved to be lifted through forklift pockets. The TM53 low profile and TM114 models have integrated lifting eyes and lifting lugs which allows the tank to be lifted - even when full!



The Perfect Companion for your Truck

The TruckMaster tanks are designed for minimal footprint and height. It makes them the perfect add-on to your truck, as they only occupy a small space on the truck-bed and can be tied down between the wheel arches of the pick-up.

TM53 low profile



Capacity	53 gallons
Length	47 inches
Width	34 inches
Height	20 inches
Weight	102 lbs

TM79



Capacity	79 gallons
Length	24 inches
Width	32 inches
Height	35 inches
Weight	100 lbs

TM114



Capacity	114 gallons
Length	47 inches
Width	34 inches
Height	36 inches
Weight	132 lbs

Specification Options

TruckMaster®

DESCRIPTION / CAPACITY	TM53	TM53 LOW PROFILE	TM79	TM114
Level gauge				•
Ball valve on suction line		○		•
Suction line with mesh filter	•	•	•	•
12 V DC pump (max. flow rate 13 gal/min)*	•	•	•	•
19' 8" power cable with battery clamps	•	•	•	•
12' 2" flexible delivery hose	•		•	
13' 2" flexible delivery hose		•		•
Automatic nozzle	•	•	•	•
Lid with integrated lock		•		•
Lid with lockable latch (padlock not provided)	•		•	
Lid with gas strut support				•
Vacuum and pressure relief vent	•	•	•	•
4 lifting lugs		○		•
Battery powered LED lamp		○		•
24 V DC pump (max. flow rate 13 gal/min)*	○	○	○	○
24/12 DC pump (max. flow rate 19/9 gal/min)*				○
12 V DC pump (max. flow rate 22 gal/min)*				○
Digital flowmeter fixed to the pump		○		○
Digital flowmeter fixed to the nozzle	○	○	○	○

● Standard accessories ○ Optional accessories *Maximum across pump flow rate as defined by pump manufacturer. Actual flowrate will be less.



Head Office
Kingspan Water and Safe Storage Inc.
100 Metro Drive, Terrell, Texas, 75160, USA
T: +1 (972) 210 4086
E: tankinfo.na@kingspan.com

The warranty is valid only if the product is used in accordance with the instructions given in the user manual and only if used for the intended purpose. Any modifications to the product without the written consent of the producer may render the warranty invalid. All included pictures are for illustration purposes only. We take every care to ensure that the information in this document is accurate at the point of publication, but with continuous product development, details are subject to alteration without notice.

